



Shell Motor Oil 10W-40

Synthetic Technology Motor Oil - Provides Reliable Engine Protection

DESIGNED TO MEET CHALLENGES

Main Applications

Shell Motor Oil 10W-40 can be used for gasoline and diesel engines requiring API SL/CF performance standards.

Specifications, Approvals & Recommendations

- API SL/CF

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties			Method	Shell Motor Oil 10W-40
Kinematic Viscosity	@100°C	cSt	ASTM D445	14.3
Kinematic Viscosity	@40°C	cSt	ASTM D445	94.8
Density	@15°C	Kg/m	ASTM D4052	874
Flash Point		°C	ASTM D93	210
Viscosity Index			ASTM D2270	155
Pour Point		°C	ASTM D97	-33
CCS Viscosity	@-25°C	cP	ASTM D5293	6470

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

This product is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from www.epc.shell.com

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Advice

Advice on applications not covered here may be obtained from your Shell representative.